





38ZWC15X-1

DINGS' MOTION DATE CODE

REV	DATE	DESCRIPTION	BY
00	20250903	INITIAL RELEASE	LIU JIN



DETAIL E



## NOTES:

1. The peak torque in the list is based on the steady state test of the motor at room temperature;
2. The motor performance parameters in the list are based on the open-loop drive of Dingzhi Company.

RATED VOLTAGE	VDC	48	DIELECTRICAL STRENGTH	1200V 50Hz 1s 3mA
RATED TORQUE	N·m	0.1	INSULATION RESISTANCE	50MΩ 20°C
RATED SPEED	RPM	10470±10%	MOUNTING TYPE	-
RATED CURRENT	A	2.75±10%	DUTY TYPE	-
RATED POWER	W	110	COOLING TYPE	IC410
PEAK TORQUE	N·m	0.32	PROTECTION GRADE	IP00
POLE PAIRS	-	7	INSULATION CLASS	F
WEIGHT	g	53 (参考)	ROTOR INERTIA	0.0101 kgcm <sup>2</sup>

THIS DRAWING IS ONLY CONDITIONALLY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POSSESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER IN THIS DRAWING ARE AND REMAIN, EXCEPT AS MAY BE OTHERWISE INDICATED BY WRITTEN NOTICE HEREON, THE EXCLUSIVE PROPERTY OF SAID CORPORATION. THIS DRAWING MAY BE REPRODUCED ONLY BY LICENSEES AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSED MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSEES AND ASSOCIATE CONTRACTORS.

UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE IN MILLIMETERS  
AND TOLERANCES ARE AS BELOW

L I N E A R

A N G U L A R

0 - 3

±0.2

0 - 10

±1.5°

3 - 6

±0.5

10 - 50

±1°

6 - 30

±1

50 - 120

±0.5°

30 - 120

±2

120 - 400


±0.25°

38ZWC15X-1

DINGS' 勤智

SIZE A4

SCALE 1:1



UL1332  
20AWG

PHASE U	YELLOW
PHASE V	RED
PHASE W	BLACK